




Imagine Series Specifications



Available in Dark Cherry Wood Veneer, Black Ash Wood Veneer, Walnut Wood Veneer, Gloss Black or Gloss White.*

*Some finishes may not be available in all countries.

Imagine Series



	Imagine T2 Tower	Imagine T Tower	Imagine B Bookshelf	Imagine mini Bookshelf	Imagine mini c Centre	Imagine C Centre	Imagine S Surround
Frequency Response	(Anechoic Chamber)						
On Axis @ 0°±3dB On Axis @ 0°±1 1/2dB Off Axis @ 30°±1 1/2dB LF Cutoff -10dB	34-23,000Hz 36-20,000Hz 36-10,000Hz 29Hz	38-23,000Hz 42-20,000Hz 42-10,000Hz 35Hz	52-23,000Hz 55-20,000Hz 55-10,000Hz 48Hz	55-23,000Hz 65-20,000Hz 65-10,000Hz 50Hz	55-23,000Hz 65-20,000Hz 65-10,000Hz 50Hz	52-23,000Hz 55-20,000Hz 55-10,000Hz 46Hz	65-23,000Hz 68-20,000Hz 68-10,000Hz 58Hz
Sensitivity	(1W (2.83V) @ 1M, IEC-Filtered pink noise, C-weighted)						
Anechoic Chamber Listening Room	88dB 90dB	88dB 90dB	87dB 89dB	85dB 87dB	86dB 88dB	87dB 89dB	87dB 89dB
Impedance							
Nominal Minimum	8 Ohms 4 Ohms	8 Ohms 4 Ohms	8 Ohms 4 Ohms	8 Ohms 4 Ohms	8 Ohms 4 Ohms	8 Ohms 4 Ohms	8 Ohms 4 Ohms Bipole/Dipole
Input Power	(RMS, Clipping <10% Time)						
Recommended Program	20 - 300 Watts 300 Watts	20 - 200 Watts 200 Watts	20 - 150 Watts 150 Watts	10 - 80 Watts 60 Watts	10 - 80 Watts 60 Watts	20 - 150 Watts 150 Watts	20 - 150 Watts 150 Watts
Acoustic Design							
Tweeter (Nominal)	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet	2 x 1" (25mm) Titanium Dome with Ferrofluid Neodymium Magnet
Midrange (Nominal)	4" (102mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround						
Woofer (Nominal)	3 x 5 1/4" (133mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround	2 x 5 1/4" (133mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround	5 1/4" (133mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround	4" (102mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround	2 x 4" (102mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround	2 x 5 1/4" (133mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround	2 x 5 1/4" (133mm) Clay/Ceramic reinforced Polypropylene Cone Rubber Surround
Crossover	500Hz, LR4, 1,800Hz LR4	1,800Hz, LR4, 800Hz	1,800Hz, LR4	2,200Hz, LR4	2,200Hz, LR4	1,800Hz, LR4	2,000Hz, B3
Internal Volume	1.12 cu ft (31.8L)	1.0 cu ft (29L)	0.27 cu ft (7.7L)	0.1 cu ft (2.8L)	0.16 cu ft (4.5L)	0.54 cu ft (15.4L)	0.22 cu ft (6.2L)
Design Type	Transitional 5-way Triple Port Bass Reflex	Dual Port Bass Reflex	Bass Reflex	Bass Reflex	Bass Reflex	Bass Reflex	Sealed
Size (W x H x D)	(Gross Dimensions)						
	8 3/8 x 40 5/8 x 13 5/8" ** 210 x 1,031 x 346mm	8 3/8 x 37 1/4 x 13 5/8" ** 210 x 945 x 346mm	7 1/2 x 12 7/8 x 12 1/8" ** 190 x 324 x 305mm	5 3/4 x 9 1/4 x 8 3/8" ** 143 x 234 x 212mm	14 x 6 x 8 1/2" ** 353 x 152 x 213mm	20 5/8 x 7 1/2 x 13 5/8" ** 521 x 190 x 346mm	10 3/4 x 12 3/4 x 7 1/8" ** 273 x 321 x 178mm
Weight							
Net Shipping	42.6lb (19.4kg)/each 59lb (26.8kg)/each	40.6lb (18.5kg)/each 47.8lb (21.7kg)/each	17.2lb (7.8kg)/each 38lb (17.3kg)/pair	6.5lb (3kg)/each 15.5lb (7kg)/pair	9.8lb (4.5kg)/each 12.3lb (5.6kg)/each	26.8lb (12.2kg)/each 30lb (13.6kg)/each	16.3lb (7.4kg)/each 37lb (16.8kg)/pair
Finish							
	Black Ash, Dark Cherry, Walnut Wood Veneer, Gloss Black or Gloss White*	Black Ash, Dark Cherry, Walnut Wood Veneer, Gloss Black or Gloss White*	Black Ash, Dark Cherry, Walnut Wood Veneer, Gloss Black or Gloss White*	Black Ash, Dark Cherry, Walnut Wood Veneer, Gloss Black or Gloss White*	Black Ash, Dark Cherry Walnut Wood Veneer, Gloss Black or Gloss White*	Black Ash, Dark Cherry Walnut Wood Veneer, Gloss Black or Gloss White*	Black Ash, Dark Cherry Walnut Wood Veneer, Gloss Black or Gloss White*

*Some finishes may not be available in all models and/or all countries.

**Non-metric measurements are approximate.

All specifications are subject to change without notice. Non-metric measurements are approximate. PSB Speakers will not assume any liability for errors in this brochure which may result in errors being made by retailers, custom installers, cabinet makers or other end users based on information contained in this document. PSB Speakers reserves the right to change specifications or features without notice. © 2012 PSB Speakers, a division of Lenbrook Industries Limited. PSB is a registered trademark of Lenbrook Industries Limited. All rights reserved. No part of this publication may be reproduced, stored or transmitted in any form whatsoever without the written permission of PSB Speakers. 12-019 Printed September 2012.

www.psbSpeakers.com